

### Architectural Specifications

#### PRODUCT

abCOR LINEAR RL 6 is a acoustic panel using a unique slot-ted perforated design, giving a very uniform appear-ance when used as wall or ceiling treatment.

The abCOR LINEAR panels are made up of an **MDF core** sandwiched between a **surface layer** of real wood veneer, melamine or paint and an **acoustic fleece**

#### DIMENSIONS

**Perforation Face:** 6 mm wide slots 8,5mm long  
**Open area:** 9.1 % perforated face  
**Thickness:** 12mm  
**Weight:** 9,5 kg / m2  
**Standard sizes:**  
 Planks - 600 x 600, 1200 x 600mm ( Standard )  
 Panels - Other sizes available upon request

#### MATERIAL SOURCE

All material used in the production of **abCOR LINEAR** panels are from **European sources** . All manufacturing is done here in Ireland to the highest quality norms.


Our wood product components are sourced from providers with environmentally friendly practices and were required or request we supply certified

#### EDGE DETAIL


The **abCOR LINEAR** range of panels can be machined to various edge profiles;

A range of edge profiles are available to suit the designers / architects' preferred look and installation method.

TG 03 - Tongue & G with 3mm Gap



RV 20 - Reveal, 20mm Shadow Gap





TGV 02 - Tongue & Groove V Joint



TBV 03 - Bevelled Joint 3mm Gap



WHITE PAINTED FINISH - SEMI-MATT



#### FINISHES

The **abCOR LINEAR** acoustic panels are available in a varying range of sur-face finishes from real wood ve-neers, melamine and HPL to high quality painted surfaces.

##### Real Wood Veneers

- All wood species - First quality

##### Man made veneers




- Reconstituted veneers - Good colour match


##### Melamine

- Wood grain, Solid colours - Budget

##### Laminates ( HPL )

- Wood grain , Solid colours - High wear





Finish melamine and veneer




E: 1/5


**MACHINING DETAIL**

E: 1/4

**SOUND GRAPHIC**



RC 6




Drawn by: MJB

Approved: Approved:

Date: 11-12-2013

### Acoustic Performance




Panels are tested in a laboratory using 40mm of acoustic insulation, 30kg/m<sup>3</sup> and with an air gap of 250mm.  
by ACARMA - ACUSTICA ARQUITECTONICA Y DEL MEDIO AMBIENTE

### Absorption

125	250	500	1000	2000	4000	NRC
0.38	0.75	0.75	0.85	0.59	0.45	0.74

**NRC Value: 0.74**  
**Absorption Class C**



### Acoustic Absorption

The design and perforation type, size and quantity make the abCOR LINEAR RC 6 is an absorbent panel often difficult to achieve in wooden panels.

Good for the mid to higher frequency ranges.

## Technical Specifications

### INSTALLATION

The abCOR LINEAR panels are designed to be installed using the abCOR LINEAR edge profiles or half perforation system.

Products are to be installed to manufacturers recommendations by experienced installers.

Material should rest for 2 to 3 days prior in the site conditions before carrying out the installation work. In new buildings with fresh concrete and plaster, installation should not be carried out until the relative humidity has equalised.

An expansion joint of 2-3mm should be allowed for every

### IMPACT RESISTANCE - HIGH

Medium density fibreboard panels used in our acoustic products are impact resistant and ideally suited for use in high traffic areas such a corridors and lecture theatres in schools, universities and public spaces.

### HANDLING AND STORAGE

abCOR LINEAR acoustic panels should be stored in a dry environment, flat and covered to protect them from dust and dirt.

Package should be opened and panels allowed to acclimatize prior to installation.

### TECHNICAL ADVICE

Our qualified installation and acoustic engineers are available to assist with technical advice on specifications and installation requirements at

### FIRE PERFORMANCE - HIGH


The core material used in Fire Rated panels is Euroclass Bs2d0 Mdf . When veneer is the finish we also use a lacquer, Euroclass Bs2d0.

When manufacturing for fire rated requirements the factory complies with the certificate held in accordance to UNE-EN 13501-1:07 " classification of perfor-


### APPLICATIONS

The abCOR LINEAR RC 6 panel is designed for use in areas requiring a high level of sound absorption as acoustic treatment.


Conference Centres      Auditoria      Banquet Halls  
Airports                      Universities      Hotels








Finish melamine and veneer




E: 1/5

**MACHINING DETAIL**

E: 1/4



**SOUND GRAPHIC**



Drawn by: MJBP

Approved: Approved:

Date: 11-12-2013